Atlas Snack Food Bagmakers

Combine the fastest available bagmaking speeds with these productivity-boosting advances

- Highest quality seals owing to the industry's widest choice of sealing mechanisms and Ishida's special backseal unit
- Better film-feed control thanks to servo-motor controlled pull down system and unique strain-gauge load cell
- Neater, faster product insertion with Ishida weigher-bagmaker chute synergy and unique bag-former geometry


Increase operator productivity by making learning and operation easier and faster


- Touch panel RCU offering standardised operating screens, minimum keystroke operation, 'no mistake' product image registration and
- Film splicing and film changeover now easier and faster than ever before
- Using latest USB interface technology for ease of data management


Pick the integrated approach that will maximise your packing speed and yield


- Combine Atlas bagmaking with Ishida weighing for optimised results and
- Choose the weigher-bagmaker configuration that best meets your product and floorspace requirements
- Benefit from total integration, including seal testing and checkweighing

Cifiti							
Specificati	ions						
Model		Atlas-204	Atlas-224	Atlas-124	Atlas-124C	Atlas-114C	
Running speed*		up to 200bpm	up to 200bpm	up to 250bpm	up to 250bpm	up to 125bpm	
Bag Size	Width	101.6 - 330mm	101.6 - 330mm	75 - 230mm	75 - 230mm	75 - 230mm	
	Length	127 - 711mm	127 - 711mm	75 - 533mm	75 - 533mm	75 - 533mm	
Film Size	Max. roll width	685.8mm	685.8mm	483mm	483mm	483mm	
	Bore of film roll core	76.2mm	76.2mm	76.2mm	76.2mm	76.2mm	
Product		Snack foods such as potato chips, extruded snacks, corn chips, tortilla chips, popcorn, nuts and seeds					
Film Feeding Motion		Continuous/Intermittent		Continuous			
Machine	Width		990mm		990mm		
Size	Height		2000mm		1825mm		
	Length		2160mm		1780mm		
Power Supply Power Voltage**		3 phase AC200-208V 50/60hz 3 phase AC220V-480V (Built-in Transformers)					
Allowable Voltage Fluctuation		±10%					
Air Supply		0.5 - 1MPa (5.1 - 10.2kgf/cm2) 60N/min.					
Net Weight		1300kg			1200kg		
Operational Temperature		32-104°F (0-40°C) RH30-70% non-condensing					
Options		Data printer, Air nitrogen switch and solenoid assembly for Air Jet, Splicing plate film knife kit, Product poker					
Sealing Jaw Motion		Twin jaw D-motion	Twin rotary jaw	Twin rotary jaw	Twin rotary jaw	Single rotary jaw	











Tel: +44 (0)121 607 7700 Tel: +40 (0)21 589 73 52 Tel: +7 499 272 05 36 Fax: +44 (0)121 607 7888 Fax: +40 (0)21 310 34 22 Fax: +7 499 272 05 37

Fax: +27 (0)11 976 2012





Ishida Europe: understanding and tackling the weighing and packing line challenges you face

- Unique engineering expertise, combined with practical industry knowledge in your sector
- Global applications experience, including snacks, meat, poultry ready meals, fresh produce, dry and frozen foods, bakery confectionery and pasta
- R&D resources and commitment to support both continuous improvement and major innovation
- Solutions include multihead weighers, distribution and topping systems, snack food bagmakers, tray sealers, X-ray inspection systems, checkweighers, weigh-price-labellers, seal testers, pick-and-place systems, complete lines, project management





Atlas Snack Food Bagmakers

The advanced features behind Atlas productivity

Weigher-bagmaker chute synergy

Weigher discharge chute and bagmaker entry funnel are designed and made by a single manufacturer (Ishida) based on extensive experience. Product flow across the interface is optimised for speed and smoothness.

Bag-former geometry

Original shape plus N, gas flushing system prevent product from being blown upward, ensuring even product charging.

Servo motor-controlled vacuum pull-down belt

Enables precise film feeding, even at high speed.

Backseal unit

Rotating hot steel band, synchronised exactly with film speed, delivers the world's smoothest vertical seal, which is instantly cooled by an air blower. Complete integrity assured for both fin and lap seals.

Ishida stripping device

Clears product from the area where the sealing jaws will meet the film, ensuring an intact seal and dramatically reducing pack waste at high

Increase operator productivity with easier and faster learning and operation

An interface that really communicates

- Touch-panel RCU with highly visual, icon-based screens
- Standardised Ishida operating screens make learning simpler
- Tab system eases navigation from one screen to another
- Packs can be photographed and colour images stored to ensure correct settings/presets are chosen
- Multi-language support to accommodate most operators

Film splicing and changeovers made simpler

- A special plate captures and holds the film for splicing, saving time and giving more consistent results
- During changeovers, the new film is automatically centred once the bag width is entered on the RCU
- No need to input the new bag length: Atlas automatically calculates it, using the regmark sensor

Simple, secure data management

Backup and interchange of data is easy and secure, using the latest USB technology.







your packing speed and yield Combine with Ishida weighing for optimised results

and single-source convenience

Choose the integrated approach that maximises

Ishida offers fully integrated, single-manufacturer multihead weigher and bagmaker combinations for snacks. Years of experience with both machines have enabled Ishida to optimise the physical and electronic interfaces to enhance speed and reduce weighment spread. Equally important, one company takes full responsibility for the performance of the combination.

Choose the weigher-bagmaker configuration that best meets your product and floorspace requirements


Atlas Snack Bagmakers can be deployed in two different configurations (see below). In a direct overmount setup, each bagmaker has a weigher mounted directly on top of it. In a twin-bagmaker configuration, one weigher serves two bagmakers, designed to sit together as a compact unit.

A new development is the Ishida RV-218WB, an oval multihead weigher designed specifically for this purpose, delivering very high packing speeds (see right).

Benefit from total integration, including seal testing and checkweighing

The benefits of single-manufacturer sourcing can be extended to provide complete integrated packing lines, including seal checkers and checkweighers. A single touchscreen makes it fast and easy to change settings and presets for a whole line. Metal detectors and printers can also be integrated.





RV-218 multihead weigher helps to minimise the spread of each weighment that enters either bagmaker, while achieving speeds of up to 300 wpm.

*The Ishida Ceramic Knife sharply reduces bagmaker maintenance. Blade life typically, as demonstrated on customer sites, has been at least two years. This contrasts with conventional bag-cutting mechanisms, which need changing every 10 weeks.

Sealing mechanism (unique choice)

and adjustable bag inflation.

Choose rotary jaw motion, with long lasting ceramic knife*, for highest possible speeds. Choose D-motion for longer sealing time (thicker film) Strain gauge load cell

and assure pack quality.

Provides real-time detection of the load applied by the film to

the dancer rollers. Automatically controls the film feed rate to

maintain constant film tension, helping to avoid film breakage