




NEW IX-EN-4062

Latest X-ray inspection technology for entry level users makes for an easy investment choice


Using the latest in X-ray technology, this system is the most affordable choice for ensuring product quality. This model is most purposeful in handling light, thin products, possessing the required sensitivity to accurately detect faults and contaminants.







Specifications		IX-EN-4062
Tunnel aperture	Width	400mm
	Height	150mm
Construction	Material	SUS304 (Polished surface – Bead blast option)
	IP Rate	Conveyor chamber: IP66 / Enclosure: IP54 (IP65, option)
Machine dimensions		800mm(L)x870mm(W)x1745mm(H) (*1) (Floor to Signal Tower: 1960mm)
Machine weight		290kg
Conveyor	Dimensions	800mm(L) x 430mm(W) (1800mm optional (L))
	Belt height	900mm +/- 50mm (*2)
	Speed	10-60m/min
	Loaded weight	5kg (higher weight is optional)
Product length		20~450mm (optional 1000mm) (*3)
Minimum spacing between products		30mm (*3)
Power supply		Single phase: AC200-240V 50/60Hz 450W (*4)
X-ray	Tube voltage	30/35/40/45/50/55kV
	Tube current	1mA
	Output	Max: 55W
Line sensor		0.6mm
X-ray protection		Protective curtains (*5)
X-ray emissions		Machine meets local regulations
Working environment	Temperature	0-33°C (*6)
	Humidity	30-85%RH



	- ()
Height (*7)	Width
0	400
10	387
20	375
30	363
40	350
50	338
60	326
70	314
80	301
90	289
100	277
110	264
120	256
130	240
140	228
150	215

Product Size (mm)

Design and specifications are subject to change without notice.

- (*1) This dimension shall be applied in case of 900mm belt height.
- (*1) This dimension shall be(*2) Other heights optional.

Inspection area
The figures show the permissible inspection range. Portions of the product which are not within the shaded area are not irradiated.

- (*3) This dimension should be followed under Snap-Mode only. In case of Bulk-Mode, not applied.
- (*4) 450W is applied in case of no specific ancillary.
- (*5) The material of protection curtain is tungsten, and curtain is detachable.
- (*6) If the room is hotter than 33°C, the air conditioner shall be arranged as a chargeable option. In this case, the maximum temperature is 40°C.
- (*7) The inspection width against the height is approximate value.













Ishida Global standard X-ray series



Benefits of an X-ray inspection system

X-ray inspection has several key benefits, especially for food producers, that are fundamentally linked to safety and quality:



Brand protection

Customers will trust the product



Food safety

The food is free of foreign bodies and safe to eat



Cost savings due to no product recalls and customer complaints

• Fewer recalls and customer complaints lead to less fines



Can do much more than just finding foreign bodies:

- Counting components
- Weight estimation
- Checking fill level
- Detecting flaws such as missing or broken items
- Measuring product size
- Sealing control

All these functions in one machine lead to a cost-effective and efficient performance



Ishida X-ray integrated solutions

Our systems are ergonomically designed, from the reject bin position to the different types of reject units, to be easily integrated into your production line without disruption.

Chocolate bars

Cereal bars









Ferrous/Non-ferrous

Stainless Steel

Sliced cheese



Examples of thick products



High density and



Stainless Steel Ferrous/Non-ferrous







ISHIDA EUROPE LIMITED Kettles Wood Drive

Woodgate Business Park Birmingham B32 3DB United Kingdom Tel: +44 (0)121 607 7700

Fax: +44 (0)121 607 7888

info@ishidaeurope.com

ISHIDA CZECH REPUBLIC

Tel: +420 317 844 059 Fax: +420 317 844 052 info@ishidaeurope.cz

ISHIDA ROMANIA

Tel: +40 (0)21 589 73 52 Fax: +40 (0)21 310 34 22 info@ishidaeurope.ro

ISHIDA FRANCE

Tel: +33 (0)1 48 63 83 83 Fax: +33 (0)1 48 63 24 29 info@ishidaeurope.fr

ISHIDA RUSSIA AND CIS

Tel: +7 499 272 05 36 Fax: +7 499 272 05 37 info@ishidaeurope.ru

ISHIDA GERMANY

Tel: +49 (0)791 945 160 Fax: +49 (0)791 945 1699 info@ishida.de

ISHIDA SOUTH AFRICA

Tel: +27 (0)11 976 2010 Fax: +27 (0)11 976 2012 info@ishidaeurope.com

ISHIDA MIDDLE EAST

Tel: +971 (0)4 299 1933 Fax: +971 (0)4 299 1955 ishida@ishida.ae

ISHIDA SWITZERLAND

Tel: +41 (0)41 799 7999 Fax: +41 (0)41 790 3927 info@ishida.ch

ISHIDA NETHERLANDS

Tel: +31 (0)499 39 3675 Fax: +31 (0)499 39 1887 info@ishida.nl