



NEW IX-GN-2444


Advanced X-ray inspection with the perfect balance of high performance detection sensitivity and low operating costs

Advanced X-ray detection that strikes the balance between optimal sensitivity and economic operation. Suitable for a wide range of products, this X-ray inspection system can be adapted to virtually any application.


Dimensions in mm







Specifications		IX-GN-2444
Tunnel aperture	Width	240mm
	Height	120mm
Construction	Material	SUS304 (Polished surface – Bead blast option)
	IP Rate	Conveyor chamber: IP66 / Enclosure: IP65
Machine dimensions		800mm(L)x745mm(W)x1745mm(H) (*1) (Floor to Signal Tower: 1960mm)
Machine weight		285kg
Conveyor	Dimensions	800mm(L) x 270mm(W) (1800mm optional (L))
	Belt height	900mm +/- 50mm (*2)
	Speed	10-60m/min (optional 90m/min)
	Loaded weight	5kg (higher weight is optional)
Product length		20~450mm (optional 1000mm) (*3)
Minimum spacing between products		30mm (*3)
Power supply		Single phase: AC200-240V 50/60Hz 1150W (*4)
X-ray	Tube voltage	25/30/35/40/45/50/55/60/65/70/75kV
	Tube current	1-8mA
	Output	Max: 300W
Line sensor		0.3mm
X-ray protection		Protective curtains (*5)
X-ray emissions		Machine meets local regulations
Working environment	Temperature	Maximum operating temperature 40°C
	Humidity	30-85%RH



Inspection area The figures show the permissible inspection range. Portions of the product which are not within the shaded area are not irradiated.

Product Size (mm)			
Height (*6)	Width		
0	240		
10	234		
20	228		
30	222		
40	216		
50	210		
60	204		
70	198		
80	192		
90	186		
100	180		
110	175		
120	169		

Design and specifications are subject to change without notice

- (*1) This dimension shall be applied in case of 900mm belt height
- (*2) Other heights optional.
- (*3) This dimension should be followed under Snap-Mode only.
- In case of Bulk-Mode, not applied.
- (*4) 500W is applied in case of no specific ancillary.
 (*5) The material of protection curtain is tungsten, and curtain is detachable.
- (*6) The inspection width against the height is approximate value.





Ishida Global standard X-ray series



Benefits of an X-ray inspection system

X-ray inspection has several key benefits, especially for food producers, that are fundamentally linked to safety and quality:



Brand protection

Customers will trust the product

Food safety

The food is free of foreign bodies and safe to eat

Cost savings due to no product recalls and customer complaints

• Fewer recalls and customer complaints lead to less fines



Can do much more than just finding foreign bodies:

- Counting components
- Weight estimation
- Checking fill level
- Detecting flaws such as missing or broken items
- Measuring product size
- Sealing control

All these functions in one machine lead to a cost-effective and efficient performance



Ishida X-ray integrated solutions

Our systems are ergonomically designed, from the reject bin position to the different types of reject units, to be easily integrated into your production line without disruption.

Examples of uniform products



Meat

Stainless Steel

Ferrous/Non-ferrous





Examples of complex products





Sausage

Yoghurt pots





Cereals



Teflon, PVC



Stones

A group of products that are standardized or identical.

** Products which include different thicknesses, are overlapping etc.

ISHIDA EUROPE LIMITED Kettles Wood Drive Woodgate Business Park Birmingham B32 3DB United Kingdom Tel: +44 (0)121 607 7700 Fax: +44 (0)121 607 7888 info@ishidaeurope.com

IX-GN

ISHIDA CZECH REPUBLIC Tel: +420 317 844 059 Fax: +420 317 844 052 info@ishidaeurope.cz

High density and

ISHIDA ROMANIA

Tel: +40 (0)21 589 73 52 Fax: +40 (0)21 310 34 22 info@ishidaeurope.ro

ISHIDA FRANCE Tel: +33 (0)1 48 63 83 83 Fax: +33 (0)1 48 63 24 29 info@ishidaeurope.fr

ISHIDA RUSSIA AND CIS Tel: +7 499 272 05 36 Fax: +7 499 272 05 37 info@ishidaeurope.ru

ISHIDA GERMANY Tel: +49 (0)791 945 160 Fax: +49 (0)791 945 1699 info@ishida.de

ISHIDA SOUTH AFRICA Tel: +27 (0)11 976 2010 Fax: +27 (0)11 976 2012 info@ishidaeurope.com

ISHIDA MIDDLE EAST Tel: +971 (0)4 299 1933 Fax: +971 (0)4 299 1955 ishida@ishida.ae

ISHIDA SWITZERLAND

Tel: +41 (0)41 799 7999 Fax: +41 (0)41 790 3927 info@ishida.ch

ISHIDA NETHERLANDS Tel: +31 (0)499 39 3675 Fax: +31 (0)499 39 1887 info@ishida.nl

www.ishidaeurope.com (E) IX-GN-2444 07.16