

Ishida X-ray Inspection System Protecting your customer and your brand

18 -----

20





# Ishida X-ray Inspection Systems

Ishida X-ray inspection can be used at any stage in your production line to identify with the greatest accuracy and reliability when foreign bodies are contaminating your product, thus protecting your brand and reassuring your customers.

Benefits of an X-ray inspection system X-ray inspection has several key benefits, especially for food producers, that are fundamentally linked



Finds metal, glass, stone, bone, shell, rubber and dense plastics



**X** SERIES

• You as a supplier are using the state-of-the-art technology and can therefore be confident of quality

• Up-to-date records of all products including rejects, with all data and images stored securely

## How Ishida X-ray works

X-rays are used to see through objects to get a clear picture of what is inside. Ishida X-ray inspection systems are primarily used to detect foreign bodies such as dense plastic, rubber, metal, bone, shell, stones or glass to prevent them from contaminating a product.

### Principles of X-ray inspection device

X-rays are transmitted onto the product. A line sensor captures an image formed by the penetrating X-rays and a complex image analysis procedure identifies foreign material or defective/missing products.

As well as spotting any foreign bodies, X-ray machines can detect a wide range of product defects, and can also check product or piece weights.



# Highly sensitive foreign body detection using Genetic Algorithm (GA) technology

What if detection is needed for multiple types of foreign bodies in one product?

### Evolutionary image processing\* (GA)

anywhere else.

your specific challenges.

### GA benefits

- Improves sensitivity and detection rate
- No need to send product or contaminant to a manufacturer's lab everything is done on site
- No need for service engineer or operator intervention

Example: detecting foreign matter in a pack of sausages



### X-ray image with no algorithms applied





Unevolved image processing Foreign matter cannot be identified from the uneven profile of the sausages

0



Without Genetic Algorithm

GA (Genetic Algorithm) is a patented technique which is used exclusively in our IX Series. It allows you to accomplish a very high detection sensitivity on your products which cannot be accomplished

The use of GA allows the user to optimise the X-ray machine for their own unique product characteristics. Each GA can be tuned to focus on a specific foreign body that pose an inherent risk to the product. As such, every Ishida instrument can be uniquely and easily optimised to meet

X-ray image with initial applied imaging software



Image processing in evolution Background product effect is reduced enabling foreign bodies to be identified

X-ray image with final imaging software



Evolved image processing The background product effect is further reduced enabling foreign bodies to be identified



With Genetic Algorithm

# The benefits of low voltage

For contaminants of low density, such as bones in meat products, lower voltage X-rays created by using less kV show a greater difference between the elements.

Our most popular model of IX machines uses a 300W generator, which allows us to vary the kV value from 25-75kV and the current from 1-8mA (depending on the model).

The ability to vary the KV and mA gives Ishida a strong advantage in the detection of lower density foreign bodies.

The graph below shows how different materials behave with low and high levels of energy. The lower the energy, the higher the absorption difference which leads to better detection results.



### Examples with rubber ball

The image below depicts the effect of using lower voltage X-rays, with the rubber ball being more clearly visible in the right hand image, because the rubber stops a greater percentage of the X-rays penetrating through when lower energy is used.







# IX-G2 SERIES

### Dual Energy Sensor detects what other inspection systems miss

Most effective X-ray detection of low-density objects, including bone, shell, metal, glass and rubber.

- Pinpoint detection of foreign bodies under 0.6 mm thanks to enhanced G2 technology, from shell and stone, to metal and bone.
- Accurate X-ray inspection capable of handling packaged products with uneven surfaces, granular products and overlaps.
- Ergonomic, stainless steel design, making it easy to clean.







GN series provides high-performance X-ray inspections for an unrivalled range of foreign matter.

- Unrivalled versatility for a wide range of packed and unpacked products.
- GA image processing automatically generates optimal sensitivity for fast and efficient product changeovers.



False detection

complex\* products from 0-60mm

Low density foreign bodies





Poultry





Cereals

meat products











Stones Glass



Complex\*\* products (above 60mm

IX-GN

High density and ow density foreign bodies

\* A group of products that are standardized or identical. \*\* Products which include different thicknesses, are overlapping etc.

For detailed information on the applications the IX-GN series can handle, please refer to the "Foreign Body detection matrix" table on the page 15.

**IX-GN** SERIES

For detailed information on the applications the IX-G2 series can handle, please refer to the "Foreign Body detection matrix" table on the page 15.

\* Products which include different thicknesses, are overlapping etc.

## IX-G2 SERIES

IX-G2

# **IX-GN** SERIES

### The definite choice for a wide range of products

- Integrated air conditioning system.
- User-friendly 17" touch screen control.
- Ergonomic, stainless steel design, making it easy to clean.



Bread, cookies





Stainless Steel Ferrous/ Non-ferrous





**Examples of uniform products** 

Confectionerv **Examples of complex products** 



Cereals

Glass



Yoghurt pots



Teflon, PVC



Ice crea



Stones



Thin products (0-50mm) - XX62/63

Thick products (50-150mm) - XX93

High density and low density foreign bodies

High density and

ow density foreign bodies

# **IX-EN** SERIES

### Your first step into Ishida X-ray technology

The X-ray inspection system that enhances quality control on your production line, both affordably and effectively.

- Reliable inspections suitable for uniform products.
- Easy to set up and integrate into your production line.
- User-friendly 15" touch screen control.

# **Examples of thin products**



Chocolate bars Cereal bars

Stainless Steel

Stainless Steel

Ferrous/Non-ferrous







Rubber Teflon, PVC

Ferrous/Non-ferrous **Examples of thick products** 

Glass





Yoghurt pots Bread



Glass



Stone







Larger products

lissing item and high/low density foreign bodies

For detailed information about IX-EN-5592 and IX-GN-5523 series, please refer to the "Ishida X-ray differentiation" table on the page 14.

# **IX** LARGE SERIES

For detailed information on the applications the IX-EN series can handle,

please refer to the "Foreign Body detection matrix" table on the page 15.







arger products.

issing item and high lensity foreign bodies

# **IX** LARGE SERIES

## All the security of X-ray inspection for larger items





10

IX-EN

## IX-EN-5592 / IX-GN-5523

• High sensitivity and latest sophisticated X-ray inspection system for large sized products.

Ishida X-ray inspection systems IX-EN-5592 and IX-GN-5523 can be used at any stage in your production line to identify with the greatest accuracy when foreign bodies are contaminating your product, thus protecting your brand and reassuring your customer.



Teflon, PVC

Glass

Rubber



# **IX-GE**-B3043

### The highest level of inspection performance for bottled products

- Achieves industry leading sensitivity.
- The unique way that the Ishida side beam is designed means that no protective curtains are needed, ensuring perfect product transition.
- Automatic bottle pitch control.
- Easy-to-install in existing production lines.
- Small footprint.





## Hygienic

and cohesive design.

The device is HACCP-compliant (IP66), boasting an all-stainless steel structure and waterproof inspection chamber. The protective curtains and conveyor can be removed easily without tools.

### Easy removal and refitting of components

the risk of damage to the switch.



Protective curtain

### Rejector lineup

Once product with foreign body is identified, it must be rejected and moved off the main conveyor belt. Examples of some of the more commonly used reject solutions are shown below. However, the choice of rejector depends on the product and application.



Air Reject

Upright products

IX-GE

1

High density and low density foreign bodies



Pouch packaging

Stainless Steel Stones Ferrous/Non-ferrous

PET bottles

Glass

Tetra-pak

Examples of upright products

Mik

11

Cartons

For detailed information about IX-GE-B3043 series, please refer to the "Ishida X-ray differentiation" table on the page 14.

## **X-GE**-B3043

### Sealed structure for improved reliability

The system boasts airtight seals to prevent any foreign bodies from infiltrating and avoid internal faults. The stream lined air-conditioner is fitted on the main unit, for a smooth

Minimal design with clean lines



GN model is supplied with Magnetic interlock. A mechanical interlock system on other models makes the process of removing and reinstalling protective curtains extremely simple, reducing



Non-contact switch (optional)



Magnetic interlock

Pusher Reject



Slap Arm Reject

## Ishida X-ray differentiation

	IX-EN xx62/63	IX-EN xx93	IX-GN xx43/44	IX-EN-5592	IX-GN-5523	IX-GE-B3043	IX-G2 xx27
Hygiene							
Sloped surface	•	•	•	•	•	•	•
Toolless disassembling for cleaning	•	•	•	•	•	•	•
Machine rating	IP54	IP54	IP65	IP54	IP54	IP65	IP65
Inspection chamber rating	IP66	IP66	IP66	IP66	IP66	IP65	IP66
Mechanical interlocks	•	•		•		•	
Magnetic interlocks			•		•		•
Image processing							
Standard image resolution for an optimum detection on small and hard foreign bodies	•			•			
High image resolution for a better detection on small and hard foreign bodies		•			•	•	
Finest image resolution for an enhanced detection on small and hard foreign bodies			•				•
5 levels of customizable and powerful algorithms	•	•		•		•	
7 levels of customizable and powerful algorithms			•		•		•
Dual Energy technology for enhanced detection of bone and other lower density materials and improved detection in overlapping products							٠
X-ray power							
Minimized power range, perfect for thinner products	•						
Optimum power range for medium sized products		•		•			•
Full flexible power range suitable for a wide range of products			•		•	•	
Usability							
Quick production start up time (30-90 sec)	•	•	•	•	•	•	•
15" Remote Control Unit (RCU)	•	•		•		•	
17" Remote Control Unit (RCU)			•		•		•
Interfaces for saving images and statistics	USB, CF Card, Ethernet	CF Card, Ethernet	CF Card, Ethernet				

All information supplied within is correct at time of publication.

Ishida Europe pursues a policy of continual improvement due to technical development. We therefore reserve the right to deviate from information, descriptions, and specifications in this publication without notice. Ishida Europe shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance or use of this material.

## Foreign body detection matrix

				Natural				
Product type	Foreign body		Metal	Glass	Rubber	Teflon	Stone	Bone
Uniform*	Dairy	Sliced cheese					•	
		Yoghurt					•	
		Ice-cream					•	
	Confectionery	Chocolate bar					•	
		Box with chocolate					•	
		Cookies					•	
	Meat	Minced meat	• • •				• •	• •
		Steak	• • •				• •	• •
		Burger	• • •				• •	• •
	Dried fruit	Packed						
		Bulk	• • •					
Complex**	Meat	Chicken fillet	•	•	•	•	•	•
		Sausages in bag	• •					
		Overlapping burger	• •			• •		
		Sausages in bulk	• •					
	Cereal	Packed	• •					
		Bulk	• •					
	Vegetables	Green bean	• •					
		Broccoli	• •					
		French fries	• •					
	Dried fruit	Packed	• •					
		Bulk	• •	• •	• •	• •		•

Key to foreign body detection:

### 🖲 G2 😑 GN 🕘 EN

### • Optimum solution • Solution allowed



\* A group of products that are standardized or identical. \*\* Products which include different thickness, overlapping etc.



### Working with you every step of the way

Our extensive R&D investment is directed at meeting the challenges of the fast-changing food industry around the globe.

We aim to support our partners fully, from the very start of the buying process, and you will find many equipment brochures, visual animations and case studies available on our website. When you are ready to make contact, a well-resourced network of Ishida companies, distributors and agents, extending across Europe, the Middle East and Africa, can provide advice and organise demonstrations and trials. Installation is rapid and efficient. For integrated packing lines, we use proven project management techniques and methodologies, tuned to your key objectives and specifications.

A dedicated pan-European service engineering team helps to maximise the performance, functionality and reliability of our installed base. In addition, spares facilities are strategically placed throughout the territory, offering 24-hour delivery in most cases.



### helpline • spares • service • training





 ISHIDA EUROPE LIMITED

 Kettles Wood Drive

 Woodgate Business Park

 Birmingham

 B32 3DB

 United Kingdom

 Tel: +44 (0)121 607 7700

 Fax: +44 (0)121 607 7888

info@ishidaeurope.com

 ISHIDA CZECH REPUBLIC

 Tel:
 +420 317 844 059

 Fax:
 +420 317 844 052

 info@ishidaeurope.cz

### ISHIDA ROMANIA

Tel: +40 (0)21 589 73 52 Fax: +40 (0)21 310 34 22 info@ishidaeurope.ro **ISHIDA FRANCE** Tel: +33 (0)1 48 63 83 83

Fax: +33 (0)1 48 63 24 29 info@ishidaeurope.fr

ISHIDA RUSSIA AND CIS Tel: +7 499 272 05 36 Fax: +7 499 272 05 37 info@ishidaeurope.ru **ISHIDA GERMANY** Tel: +49 (0)791 945 160 Fax: +49 (0)791 945 1699 info@ishida.de

**ISHIDA SOUTH AFRICA** Tel: +27 (0)11 976 2010 Fax: +27 (0)11 976 2012

info@ishidaeurope.com

Tel: +971 (0)4 299 1933 Fax: +971 (0)4 299 1955 ishida@ishida.ae

**ISHIDA MIDDLE EAST** 

### ISHIDA SWITZERLAND

Tel: +41 (0)41 799 7999 Fax: +41 (0)41 790 3927 info@ishida.ch ISHIDA NETHERLANDS Tel: +31 (0)499 39 3675 Fax: +31 (0)499 39 1887 info@ishida.nl

www.ishidaeurope.com (E) X-RAY 08.18